



<b>Identification</b>	Type	WAA 7-0533
	Part-No.	750533

**Input**

Input signal	0–20 mA
Galvanic insulation I/O	3-way isolation
Zero /Span	Production comparison
Transmission frequency	30 Hz at 3 dB
Input characteristic impedance	100 Ω
Input voltage	0-20 mA/0-10 V

**Load Side**

	<b>750533/751533</b>	<b>750534/751534</b>	<b>750535/751535</b>
Output signal	0 – 10 V	0–20 mA	4–20 mA
Max. load impedance at I-output		400 Ω	400 Ω
Max. load impedance at U-output	>1 kΩ		
Load impedance	55 Ω	–	–
Output current	max. 21 mA		
Output signal	0 – 10 V		
Max. load impedance at U-output	>1 kΩ		
Load impedance	55 Ω		

02.04.2016 – Subject to technical modification

Part-No. 750533

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA  
 Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223  
 www.lutze.com • info@lutze.com

United Kingdom: LUTZE Ltd.

Unit 3, Sandy Hill Park  
 Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU  
 Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2  
 www.lutze.com • sales.gb@lutze.co.uk



## Technical data sheet • Interface Technology

---

Output current max. 21 mA  
Ripple <5 mV<sub>eff</sub>

---

### General

---

Nominal voltage AC/DC 24 V  
Operation voltage range DC: 16,8–30 V, AC: 19,2–28,8 V  
Rated current 13.0 mA  
Status Indication LED yellow  
Input/output protection AC/DC 30 V overvoltage, current input with PTC, short circuit-proof output  
Accuracy 0.1 % FSR (23 °C)  
Linearity error 0.10 %  
Rise time (10 - 90%) 10 ms  
Build-up time (Accuracy 1%) 30 ms  
Transmission frequency <30 Hz  
Temperature coefficient <150 ppm / K FSR  
Insulation voltage input/output 1.5 kV<sub>eff</sub>  
Housing material PA 6.6 (UL 94 V-0)  
Field installation rail TS 35 (EN 50022)  
Protection class IP 20  
Installation position Optional  
Termination Screw terminal: 0.14–1.5 mm<sup>2</sup>  
Operation temperature range -25 °C – 60 °C  
Storage temperature range -40 °C – 85 °C  
Dimensions (w × h × d) 6.2 × 90.0 × 92.5 mm  
Weight (kg/piece) 0.040 kg/piece  
Approvals cULus, Class I, Div. 2, Groups A, B, C, D T4A

02.04.2016 – Subject to technical modification

Part-No. 750533

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA  
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223  
www.lutze.com • info@lutze.com


United Kingdom: LUTZE Ltd.

Unit 3, Sandy Hill Park  
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU  
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2  
www.lutze.com • sales.gb@lutze.co.uk




SYSTEMATIC TECHNOLOGY

**Dimensions**



**PIN assignment**



75x533

**Accessories**

Accessories	Color	Article number	Type	PU
Tag holder 4×11 mm	white	681313	BZT-0411	100
Isolation plate		760809	TP 7-0809	5

**Accessories**

Accessories	Color	2-pole	3-pole	4-pole	8-pole	16-pole	PU
6 A jumper comb	red	762802	762805	762812	762822	762832	10
6 A jumper comb	white	762803	762806	762813	762823	762833	10
6 A jumper comb	blue	762804	762807	762814	762824	762834	10

02.04.2016 – Subject to technical modification

Part-No. 750533

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA

Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223

www.lutze.com • info@lutze.com

United Kingdom: LUTZE Ltd.

Unit 3, Sandy Hill Park

Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU

Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2

www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY