




- Front panel 53 x 28 mm
- Integral locking spring
- With universal connections
- Touch proof connections to VBG 4
- Mounting aperture: 50 x 25 mm

Save time switching controlling counting

Elapsed time counters BW 30 · BG 30
for panel mounting · Alternating/Direct Current



Mounting aperture: 50 x 25 mm

BW 30.18



BG 30.18



| Technical data | BW 30.18 Alternating current | BG 30.18 Direct current |
|---|--|----------------------------|
| Supply voltages (Please state when ordering) | 230 V, 50 Hz (standard) or 115 V, 50 Hz or 24 V, 50 Hz | 12–48 VDC |
| Special voltages | – | 5–24 V, 100–300 VDC |
| Other voltages | on request | on request |
| Special frequency | 60 Hz | – |
| Voltage tolerance | ±15 % | ±10 % |
| Power consumption (real power) | 0.11 W | approx. 20 mW at 12 VDC |
| Counter capacity | 99,999 h. | 99,999 h. |
| Accuracy of reading | 0.01 h. | 0.1 h. |
| Numeral height | 4.4 mm | 4.4 mm |
| Numeral colour | white, decimal figures red | white, decimal figures red |
| Operation indicator | fast-running wheel | LED |
| Permitted ambient temperature | –15°...+50°C | –10°...+50°C |
| Housing | self-extinguishing thermoplastic | |
| Mounting | Panel | |
| Type of connection | Universal: Screw, soldered and 6.3 x 0.8 mm AMP plug-type connections | |
| Type of protection (DIN EN 60529) | Front IP 65 | Front IP 65 |
| Class of protection | II (when fitted in accordance with regulations) | III (up to 48 VDC) |

Accessories

Retaining clip
715.005

| Order number | Version |
|------------------|---------------------|
| ✓ BW 30.18 | Alternating current |
| ✓ BG 30.18 | Direct current |
| ✓ Housing colour | |