

Product Information

Displays

Display GIA 0420 N



- Self-supplying, no additional auxiliary supply necessary
- Freely scalable
- Integrated self-diagnostic

Characteristics

The GIA 0420 is a microprocessor-controlled displaying device for 4..20 mA standard signals.

Any transmitter (with 4..20 mA output) can be connected to the device. The range adjustment of the GIA 0420 to the transmitter is done by entering the initial and final value and the decimal point position. No additional auxiliaries are needed for this adjustment, but the three buttons on the back side of the device.

The GIA 0420 doesn't need a separate auxiliary supply but is directly supplied by the measuring current. It has an integrated self-diagnostic which checks the device that it works correctly. This self-diagnostic together with the transmitter's check for "sensor break" and "sensor short circuit" and range exceeding or falling below ensures an optimum of operational reliability.

Technical data

Measuring input

Input signal : 4..20 mA (2-wire)
Accuracy : $\pm 0.2\%$ FS ± 1 digit
Measuring rate : 5 measurements / seconds
Voltage load : 3,5 V
Power supply : self-supplying: device is supplied directly from measuring current

Working temperature : 0..50 °C
Filter : adjustable in 3 stages
Switching output : 1x electrically isolated open collector switching output
Storage : min- / max-memory via buttons

Display

Display : LCD display
Height : 10 mm
Display range : -1999..+9999 digit
initial and final value adjustable

Connection

: 2-pole screw / clamp terminals,
max. cross section up to 1.5 mm²

Housing

: fibre-reinforced Noryl,
front screen made of polycarbonate


Protection class

: front IP54,
with optional sealing IP65

Dimensions

Housing : 24 x 48 x 65 mm (H x W x D)
Panel cutout : 21.7 x 45 mm [± 0.5 mm] (H x W)

Connection diagram



Design type

010N	Input signal: 0..20 V (3-wire) Input resistance: approx. 100 kOhm Power supply: 12..28 V, < 10 mA
ex	with ATEX protection for explosive areas

Ordering code

GIA 1. - 2.

1.	Design type
0420N	Display 0..20 mA
010N	Display 0..10 V
0420N-ex	Display 0..20 mA with Ex-protection
010N-ex	Display 0..10 V with Ex-protection
2.	Option
00	without option
IP	protection class IP65