

Operator Heads: Ø 22MM

 Technical Info (p. 103)

EMERGENCY STOP MAINTAINED - ILLUMINATED

Ø 40 EN 418 / ISO 13850


Push-pull to reset

Chrome Bezel
Part Number

Black Bezel
Part Number



L22DN10



Black bezel
Head position visible from the side with yellow collar
Compliant with the requirements of emergency stop:
EN 418 / ISO 13850

● Red

L22DN10


SELECTOR SWITCHES - ILLUMINATED

WITH HANDLE

2 positions



L21KJ30



Maintained positions - 45°

● Red
● Green
● Black



L21KG10
L21KG20
L21KG30

L22KG10
L22KG20
L22KG30

Spring return- 45°

● Red
● Green
● Black



L21KH10
L21KH20
L21KH30

L22KH10
L22KH20
L22KH30

Maintained positions - 45°

● Red
● Green
● Black



L21KJ10
L21KJ20
L21KJ30

L22KJ10
L22KJ20
L22KJ30

Spring return- 45°

● Red
● Green
● Black



L21KK10
L21KK20
L21KK30

L22KK10
L22KK20
L22KK30

Maintained positions - 90°

● Red
● Green
● Black



L21KL10
L21KL20
L21KL30

L22KL10
L22KL20
L22KL30

Maintained positions - 90°

● Red
● Green
● Black



L21KM10
L21KM20
L21KM30

L22KM10
L22KM20
L22KM30