BASIC M30





SHORT X2

				FLUSH		NON FLUSH	
				M12 conn	cable	M12 conn	cable
NOMINAL SWITCHING DISTANCE				15mm	15mm	20 mm	20 mm
10-30 Vdc	PNP/NPN NO-NC	4 wires	order No.	IS-30-G0-S2	IS-30-G0-03	IS-30-H0-S2	IS-30-H0-03
				95B064500	95B063861	95B064520	95B064480
10-30 Vdc	PNP NO	3 wires	order No.	IS-30-G1-S2	IS-30-G1-03	IS-30-H1-S2	IS-30-H1-03
				95B063691	95B063681	95B063771	95B063761
10-30 Vdc	PNP NC	3 wires	order No.	IS-30-G2-S2	IS-30-G2-03	IS-30-H2-S2	IS-30-H2-03
				95B063711	95B063701	95B063791	95B063781
10-30 Vdc	NPN NO	3 wires	order No.	IS-30-G3-S2	IS-30-G3-03	IS-30-H3-S2	IS-30-H3-03
				95B063651	95B063641	95B063731	95B063721
10-30 Vdc	NPN NC	3 wires	order No.	IS-30-G4-S2	IS-30-G4-03	IS-30-H4-S2	IS-30-H4-03
				95B063671	95B063661	95B063751	95B063741
10-30 Vdc	PNP NO-NC	3 wires	order No.	IS-30-G5-S2	IS-30-G5-03	IS-30-H5-S2	IS-30-H5-03
				95B063831	95B063821	95B064450	95B064420
10-30 Vdc	NPN NO-NC	3 wires	order No.	IS-30-G6-S2	IS-30-G6-03	IS-30-H6-S2	IS-30-H6-03
				95B064430	95B064400	95B064440	95B064410
10-30 Vdc	NO-NC	2 wires	order No.	IS-30-G9-S2	IS-30-G9-03	IS-30-H9-S2	IS-30-H9-03
				95B064580	95B064540	95B064600	95B064560
20-250 Vac/Vdc	NO	2 wires	order No.	---	---	---	---
				---	---	---	---
20-250 Vac/Vdc	NC	2 wires	order No.	---	---	---	---
				---	---	---	---
20-250 Vac/Vdc	NO	2/3 wires	order No.	---	---	---	---
				---	---	---	---
Analog 0-20mA	-	3 wires	order No.	---	---	---	---
				---	---	---	---
5÷24 Vdc	NAMUR	2 wires	order No.	---	---	---	---
				---	---	---	---

Nominal Voltage	10-30 Vdc (-15/10%)	10-30 Vdc (-15/10%)	10-30 Vdc (-15/10%)	10-30 Vdc (-15/10%)
Residual Ripple	< 10%	< 10%	< 10%	< 10%
Hysteresis	< 10%	< 10%	< 10%	< 10%
Max. Output Current	200 mA	200 mA	200 mA	200 mA
Min. Output Current	---	---	---	---
Residual Current	< 10 mA	< 10 mA	< 10 mA	< 10 mA
Voltage Drop	< 1,2 V (I=100mA)	< 1,2 V (I=100mA)	< 1,2 V (I=100mA)	< 1,2 V (I=100mA)
Operation Led	Yellow	Yellow	Yellow	Yellow
Switching Frequency	200 Hz	200 Hz	200 Hz	200 Hz
Start Up Delay	< 75 ms	< 75 ms	< 75 ms	< 75 ms
Repeability	< 3%	< 3%	< 3%	< 3%
Short Circuit Protection	Present (self-resetting)	Present (self-resetting)	Present (self-resetting)	Present (self-resetting)
Electric Protection	Against polarity reversal inductive loads	Against polarity reversal inductive loads	Against polarity reversal inductive loads	Against polarity reversal inductive loads
Temperature Limit	(-25 ... +70 °C)	(-25 ... +70 °C)	(-25 ... +70 °C)	(-25 ... +70 °C)
Protection Degree	IP67	IP67	IP67	IP67
Cable Length	---	2 m	---	2 m
Cable Section	---	3 x 0,25 mm²	---	3 x 0,25 mm²
Housing Material	Nickel-plated brass	Nickel-plated brass	Nickel-plated brass	Nickel-plated brass
Weight - Cable Output	---	210 g	---	210 g
Weight - M12 Connector Output	170 g	---	170 g	---

STANDARD X2

FLUSH
M12 conn
15 mm

IS-30-E1-S2
95B067060