

Extruded heatsinks for PCB mounting

for semiconductor clip-mounting



art. no.	↔ [mm]	R_{th} [K/W]		
			...	
SK 129 25,4 ...	25.4	7.8	TO 220	
SK 129 38,1 ...	38.1	6.5	TO 220	
SK 129 50,8 ...	50.8	5.3	TO 220	
SK 129 63,5 ...	63.5	4.5	TO 220	

please indicate: **... mouting method**
STC =with solder pin
STIC =with solder pin and insulating washer
STCB=with threaded bolt M 3, brass

P = raised retaining stud, **E** = mounting method

special lengths and drillings on request

surface treatment: black anodised

for semiconductor screw-mounting



art. no.	↔ [mm]	R_{th} [K/W]		
			...	
SK 129 25,4 ...	25.4	7.8	TO 220/ SOT 32/ TO 3 P	
SK 129 38,1 ...	38.1	6.5	TO 220/ SOT 32/ TO 3 P	
SK 129 50,8 ...	50.8	5.3	TO 220/ SOT 32/ TO 3 P	
SK 129 63,5 ...	63.5	4.5	TO 220/ SOT 32/ TO 3 P	

please indicate: **... mouting method**
STS =with solder pin
STIS =with solder pins and insulating washer
STSB=with threaded bolt M 3, brass

E = mounting method

special lengths and drillings on request

surface treatment: black anodised