



hps+340/DD/TC/E/G2

scale drawing



detection zone



2 x pnp



8,000 mm

operating range	350 - 8.000 mm
design	Prozessanschluss G2
operating mode	proximity switch/reflective mode reflective barrier window mode
particularities	pressure-resistant high chemical resistance stainless steel version display process connection G2

ultrasonic -specific

means of measurement	echo propagation time measurement
transducer frequency	120 kHz
blind zone	350 mm
operating range	3,400 mm
maximum range	8,000 mm
resolution/sampling rate	0.18 mm
reproducibility	± 0.15 %
accuracy	± 1 % (temperature drift internally compensated)

electrical data

operating voltage U_B	9 - 30 V d.c., reverse polarity protection
voltage ripple	± 10 %
Leerlaufstromaufnahme	≤ 80 mA
type of connection	5-pin M12 initiator plug

hps+340/DD/TC/E/G2

outputs

output 1	switching output pnp: $I_{max} = 200 \text{ mA } (U_B-2V)$ NOC/NCC adjustable, short-circuit-proof
output 2	switching output pnp: $I_{max} = 200 \text{ mA } (U_B-2V)$ NOC/NCC adjustable, short-circuit-proof
switching hysteresis	50 mm
switching frequency	3 Hz
response time	240 ms
delay prior to availability	< 380 ms

inputs

input 1	com input synchronisation input
---------	------------------------------------

housing

material	stainless steel, plastic parts: PBT, TPU
ultrasonic transducer	coated with PTFE film, FFKM O-ring
class of protection to EN 60529	IP 67
operating temperature	-25°C to +70°C
storage temperature	-40°C to +85°C
weight	1,200 g


technical features/characteristics

temperature compensation	yes
controls	2 push-buttons + LED display (TouchControl)
scope for settings	Teach-in and numeric configuration via TouchControl LCA-2 with LinkControl
Synchronisation	yes
multiplex	yes
indicators	3-digit LED display, 2 x three-colour LED
particularities	pressure-resistant high chemical resistance stainless steel version display process connection G2

hps+340/DD/TC/E/G2

[documentation \(download\)](#)

pin assignment



order no.

hps+340/DD/TC/E/G2